



模块化
标准设计



多重
保护系统



交直流一体
安装调试高效



智能运维

参数 / 型号		Celestial Energy-2073
直流侧基本参数	电芯容量	100Ah
	模块成组	3P18S
	单簇模块数量	20pcs
	电池簇数量	6pcs
	电池系统电量	2073kWh
	电压范围	1008~1278V
交流侧基本参数	额定交流功率	6*200kW
	额定电网电压	690V
	接线方式	3W+PE
	额定电网频率	50/60Hz
	隔离方式	无隔离变压器
系统级参数	工作温度	-30~55°C
	环境湿度	0~95% (无凝露)
	工作海拔	2000m
	通讯方式	以太网、RS485、可选4G/5G移动通信
	防护等级	IP54
	冷却方式	风冷
	噪音	≤65dB
	消防	全氟己酮舱级/气溶胶+水消防+可燃气体探测+防爆通风系统
	尺寸(W*D*H)	2438*2896*6058mm
	重量	24t



昆宇电源股份有限公司

网址:WWW.COSPOWERS.COM

地址:山东省东营市东营区东七路28号

电话:0546-7768891

版权及最终解释权归昆宇电源股份有限公司所有

Celestial Energy-2073

COSPOWERS



Modular Standard Design



Multiple Protection Systems



Efficient Installation and Commissioning of AC/DC Integrated Systems



Intelligent Operation and Maintenance

Parameters/ Model		Celestial Energy-2073
DC side basic parameters	Battery Capacity	100Ah
	Module Structure	3P18S
	Module quantity in single cluster	20pcs
	Nos. of Battery Clusters	6pcs
	Battery system power	2073kWh
	Voltage Range	1008~1278V
AC side basic parameters	Rated grid voltage	6*200kW
	Wiring Mode	690V
	Rated grid frequency	3W+PE
	Rated AC power	50/60Hz
	Isolation mode	no isolation transformer
System level parameters	Operating temperature	-30~55°C
	Ambient Humidity	0~95% (no condensation)
	Working Altitude	2000m
	Communication method	Ethernet, RS485, optional 4G/5G mobile communication
	Protection level	IP54
	Cooling Method	Air cooling
	Noise	≤65dB
	Fire protection system	Heptafluoropropane/Perfluorohexane compartment level/aerosol ten water fire protection + combustible gas detection +explosion-proof ventilation system
	Size(W*D*H)	2438*2896*6058mm
	Weight	24t



Cospowers Technology Co., Ltd.

W:WWW.COSPOWERS.COM

A:No.28, Dongqi Road, Dongying City, Shandong Province, P.R.C.

T:+86-546-7768891

Copyright and final interpretation rights belong to Cospowers Technology Co., Ltd.